



WSC -100-E-5M Modular Water Sensing Cable with End Termination, 5m

Product Description

- ⁻ Detects the Presence of Liquid at any point along its length
- Able to detect Water, Mild Acid or Mild Alkaline
- Installed with Liquid Leakage Alarm System, the cable senses liquid leakage and triggers an alarm
- Modular Design with Factory Pre -Molded Connectors, one end Pre -Terminated
- Small, Lightweight and Flexible, allowing Easy Installation

Technical Specifications



| | Description | Color |
|---|---|--------|
| Α | Outer Jacket Material: Electric Polyethylene, 30 AWG Alloy Wire | Black |
| В | Outer Jacket Material: Polyethylene, 26 AWG Copper Wire | Yellow |
| С | Outer Jacket Material: Electric Polyethylene, 30 AWG Alloy Wire | Black |
| D | Outer Jacket Material: Polyethylene, 26 AWG Copper Wire | White |
| Е | Polyethylene | Blue |
| F | Outer Jacket Material: Polyethylene, 18 AWG 7/26 Steel Wire | Blue |

- Tensile Strength: 30kg
- Weight: 29g/m
- Insulation Impedance: \geq 7M Ω , DC 100V
- Wire Impedance: Copper wire 0.18 $\Omega/m \pm 10\%$ Alloy wire 13.0 $\Omega/m \pm 10\%$
- Working Conditions: Temperature -20°C ~ 60°C

Humidity 5% ~ 95% (Non -condensing)

Certifications:
EMC 61000 -6-3:2007
EMC 61000 -6-1:2007



